



VACUUM AIR TUBE (VAT) 23GX OVERHEAD DRIVE-UP SYSTEM

THE BEST RETROFIT SOLUTION FOR TODAY'S REMOTE RETAIL BANKING

The Diebold VAT 23GX drive-up system is a feature-enriched, 4.5" overhead banking system designed for durability, sophistication and reliability. This low-maintenance design, with integral blower in the customer unit, is ideal for new sites or as a refresh solution for your current drive-up system. You can choose to upgrade the operator unit, customer terminal or both.



DESIGNED TO LAST

- Modernized appearance enhances the level of sophistication and technology delivered to the consumers
- Retrofittable design offers a convenient refresh solution for your current drive-up system
- Allows for continuous use by completing more than a quarter of a million round-trip cycles without failure



CUSTOMER-FRIENDLY

- 15" sunlight-viewable monitor promotes efficiency by providing clear, two-way video communication between the teller and the consumer
- 816 Audio™ System offers superior two-way, full-duplex communication between teller and consumer
- Customer terminal features dual-height control CALL/SEND buttons and a raised interface for convenient reach



VAT 23GX OVERHEAD DRIVE-UP SYSTEM

OPTIONAL 15" SUNLIGHT-VIEWABLE MONITOR

The VAT 23GX features a 15" sunlight-viewable monitor – the largest in the industry. It permits clear viewing in high ambient light conditions, including direct sunlight. Incorporating this large monitor onto the customer terminal promotes efficiency by providing clear, two-way video communication between the teller and the customer. When combined with the built-in 816 Audio System, tellers and customers experience superior two way video and audio communication.

ADAPTS TO NEW OR EXISTING SITES

The small 10.75" (27.31 cm) footprint of the customer terminal allows installation of the system on virtually any new or existing drive-up island. The tubing with compact 20" (50.8 cm) radius bends and dual blowers is installed overhead, eliminating the need for costly excavation and ensuring quiet operation. The wiring can be installed overhead or underground.

OPERATOR UNIT

The VAT 23GX upsend operator unit is suspended over the teller station to ensure that customer transactions are processed quickly and efficiently. It allows the teller to power on, power off, close and lock the system from within the facility.

CONVENIENT CUSTOMER TERMINAL

The VAT 23GX customer terminal features an enhanced ergonomic design that encompasses dual-height CALL/SEND buttons and a raised customer interface. These features improve a customer's view and reach, and have been designed for all vehicle types. An optional base raises the terminal for convenient access from vans, SUVs and trucks.

SPECIFICATIONS

OPTIONS

- Customer terminal base riser 8"H (20.32 cm)
- External customer privacy handset
- One-way or two-way CCTV

LISTINGS AND APPROVALS

- Classified for UL 345R Safety of Information Technology Equipment
- UL tested to the following standards:
 - UL114 Office Appliance & Business Equipment
 - UL50 Rain Test Specification

CUSTOMER TERMINAL

- 10.75"W x 10.75"D x 55.37"H (27.31 cm x 27.31 cm x 140.64 cm)
- Operating temperature: -30°F to 131°F (-34°C to 55°C)
- Humidity: 15% to 100% non-condensing
- Integral door rail heater
- Integral blower

SUSPENDED UPSEND OPERATOR UNIT

- 9"W x 9.43"D x 28.375"H (22.86 cm x 23.97 cm x 72.07 cm)
- Operating temperature: 50°F to 100°F (10°C to 37.8°C)
- Humidity: 15% to 80% non-condensing

TUBING

Standard 4.5" (11.43 cm) diameter tubing with 20" (50.8 cm) radius bends. Available in PVC and steel.

PROPULSION DESIGN

Blower package is located in the customer terminal; supports payloads of up to 6 lbs. (2.72 kg). Noise level less than 68 dBA.

ELECTRICAL

115VAC, 60Hz; 11 AMP

INSTALLATION FEATURES

4.5" PVC or steel tubing installed overhead. Wiring may be installed overhead or underground in culvert or direct buried configuration.

ROHS COMPLIANT

RoHS compliant in support of an environmentally friendly solution.