



VACUUM AIR TUBE (VAT) 30GX MERCHANT DRIVE-UP SYSTEM

CONVENIENT AND RELIABLE SYSTEM FOR MERCHANT TRANSACTIONS

The Diebold VAT 30GX merchant drive-up system is a feature-enriched 8" pneumatic tube system. Ideal for new sites or as a refresh solution for your current VAT 30 systems, you can choose to upgrade the teller unit, customer unit or both - depending upon your budget and needs.



MAXIMIZE EFFICIENCY

- Exceptional payload performance, accommodates 25 pounds for up to 200 tube feet
- Unique high-capacity carrier design automatically positions, opens and closes
- Retrofittable design offers a convenient refresh solution for your existing VAT 30 drive-up systems
 - During extensive testing, the VAT 30GX system completed more than a quarter-million round-trip cycles without failure



CONSUMER-FRIENDLY

- 15" sunlight-viewable monitor promotes efficiency by providing clear, two-way video communication between the teller and the consumer
- 816 Audio™ System offers superior two-way, full-duplex communication between teller and consumer
- Customer terminal features dual-height control CALL/SEND buttons and a raised interface for convenient reach



VAT 30GX MERCHANT DRIVE-UP SYSTEM

CONVENIENCE FOR THE MERCHANT

The VAT 30GX customer terminal features an enhanced ergonomic design that encompasses dual-height CALL/SEND buttons and a raised customer interface. These features improve a user's view and reach, and have been designed for all vehicle types. An optional base riser raises the terminal for convenient access from SUV's and trucks. The carrier design promotes fast, efficient transactions. The customer and carrier doors open and close automatically and there are no carriers to remove or replace. The carrier is large enough to accept bulky transaction materials weighing up to 25 pounds.

OPERATOR UNIT

The operator unit control panel has five buttons, each with its own LED indicator. Through this panel the operator can turn power to the unit on or off; send and receive the carrier; open, close and lock the customer door; and monitor the status of the system. This added benefit allows for increased security of the contents upon arrival at the customer unit, as well as full system monitoring from the operator unit.

ADAPTS TO NEW OR EXISTING SITES

The small footprint of the customer terminal allows installation of the system at virtually any new or existing drive-up island. The tubing, with compact, 32" center line radius bends, along with dual blowers are installed overhead. The wiring can be installed overhead or underground.

15" SUNLIGHT VIEWABLE MONITOR

The VAT 30GX offers an optional 15" sunlight-viewable monitor – the largest in the industry. It permits clear viewing in high-ambient light conditions, including direct sunlight. Incorporating this large monitor onto the customer terminal promotes efficiency by providing clear, two-way video communication between the teller and the customer. When combined with the built-in 816 Audio System, tellers and customers experience superior two-way video and audio communication.

SPECIFICATIONS

CUSTOMER TERMINAL

- 12.125"W x 15"D x 65.18"H
(30.8 cm x 38.1 cm x 165.6 cm)
- **Operating temperature:** -30° F to 130° F
(-34° C to 54° C)
- **Humidity:** 15 to 100 percent non-condensing
- **Color:** Charcoal Gray

OPERATOR WORKSTATIONS

- 10"W x 14"D x 47.18"H
(25.4 cm x 35.6 cm x 119.8 cm)
- **Operating temperature:** -5° F to 100° F
(10° C to 22.8° C)
- **Humidity:** 15 to 80 percent non-condensing
- **Color:** Charcoal Gray

TUBING

Standard 8" (20.32 cm) diameter tubing with 32" (81.28 cm) center line radius bends. Available in steel only.

PROPULSION DESIGN

- Dual blowers installed overhead support payloads of up to 25 lbs. (11.3 kg).
- Noise level less than 68 dBA at the customer and operator units.

ELECTRICAL

115VAC, 60Hz; 30 Amp circuits for blowers, 15 Amp circuit for control.

INSTALLATION FEATURES

Steel tubing and blowers installed overhead.

LISTINGS AND APPROVALS

Classified to UL 345R Safety of information Technology Equipment

UL tested to the following standards:

- UL 114 Office Appliance & Business Equipment UL 50 Rain Test Specification
- Restriction of Hazardous Substances (RoHS)-compliant in support of an environmentally friendly solution.