

# ActivGuard Premium Alarm Card

Today's banking environment necessitates a comprehensive, multi-layered approach to terminal security. ActivGuard from Diebold Nixdorf makes it easier than ever to manage the various protective layers that keep ATMs safe.

Functioning as an innovative security "nerve center," ActivGuard increases efficiency and reduces cost by consolidating security functions into a single embedded system—while providing enhanced security to ensure safe transactions and inspire trust. ActivGuard features a processor-based design that acts as a central interface for all terminal security devices. It collects and logs critical information and passes it along to an external alarm system or the ATM's host processor through XFS messaging



## More Personalized

Includes more standard sensors including upper chassis door sensors, two vibration/seismic sensors, thermal sensor, safe door sensor, safe bolt work status and anti-skim detection. Alarm messages can be programmed to report or suppress alarms based on any combination of sensor inputs and security alerts.



## More Integrated

Logs all sensor signal changes for auditing purposes and bolsters internal security. Includes a built-in battery backup to power operation and vibration sensors even when the ATM power is off.



## More Available

Allows alarm mapping, as well as the ability to customize and report alarms to a central monitoring station to speed troubleshooting.



## More Efficient

Diminished installation and maintenance costs, false alarm reduction and enhanced security measures yield reduced losses.



## More Future-Ready

ActivGuard features four dry contact points for self-powered sensor inputs, such as tilt, gas or smoke detectors, which offer fraud and hazard protection.



## More Secure

Protects against today's and tomorrow's threats through a layered security approach.

# Features

## SPECIFICATIONS

- Powered, processor-based alarm card
- NVRAM to store audit logs
- Connects to external alarm panel through two 20-wire output cables
- Can be programmed to report up to 12 individual alarm conditions
- Reports alarm conditions to external alarm panel
- Reports sensor condition via XFS messaging

## SECURITY

- Mounted in-system safe
- Includes cable supervisor loop
- Rolling audit log of sensor status

## RELIABILITY

- Factory installed sensors
- Sensors serviced by DN
- System powered with dedicated battery backup for 48+ hours of operation during power outages

## SYSTEM AVAILABILITY

- All DN Series™ ATMs



<b>100D</b> Indoor Mono-Function Cash Dispenser	<b>200</b> Lobby Cash Dispenser or Recycler with Check or Coin Option	<b>400</b> Lobby Multi-Function Cash Dispenser or Recycler Option	<b>230</b> Outdoor Walk-Up Cash Dispenser	<b>150</b> Outdoor Mono-Function TTW Cash Dispenser	<b>250</b> Outdoor TTW Cash Dispenser or Recycler	<b>450</b> Outdoor TTW Multi-Function Cash Dispenser or Recycler	<b>470</b> Outdoor TTW Drive-Up Multi-Function Cash Dispenser or Recycler	<b>490</b> Outdoor Island Drive-Up Multi-Function Cash Dispenser or Recycler
--	--	--	--	--	--	---	--	---

To learn more, visit [DieboldNixdorf.com](http://DieboldNixdorf.com).