

DN Series® Night Drop Depository



Envelope Deposit Sidecar for Fast and Easy Deposits

Deliver convenient envelope-based deposit services to both consumers and small businesses, allowing for more efficient cash, check and coin deposits in a single deposit operation. Complement service cash automation for all branch locations with the DN Series® Night Drop Depository Sidecar.

DN Series® Night Drop Depository Sidecar hosts a high-capacity envelope deposit module in a separate safe that can flank an existing DN Series® 200 indoor lobby or 250 outdoor TTW cash dispenser or cash recycler to allow fast and easy deposit of notes, coins and cheques through an envelope.



More
Personalized

Easy handling through comfortable and attractive design.



More
Integrated

Seamless connection of the sidecar to DN Series® 200 and 250 systems and integration into your bank's ecosystem.



More
Available

A specialized and proven deposit mechanism makes the deposit sidecar more available.



More
Efficient

Allow customers to make envelope deposits at any time, day or night.



More
Future-Ready

Our scalable, modular platform offers the flexibility to meet consumers' demands today, and in the future..



More
Secure

Motorized anti-vandalism shutter with internal mechanical protection.



More
Sustainable

Built for a greener future: DN Series® minimizes power use, reduces service and CiT trips, and optimizes resources—supporting your sustainability goals at every step.



INSTALLATION

- Window frame for rear-load system installation indoor or outdoor through-the-wall

CHASSIS

- Deposit module mounted into a separate safe which can flank an existing DN Series® Cash dispenser or cash recycler

DEPOSIT PROCESSING

- Motor-driven deposit mechanism
- Motorized shutter solution
- Anti-fishing and anti-trapping provision
- EN1143-2 "Deposit Mechanisms" certified
- Envelope deposits into the safe
- Volume inside safe up to 120 liters
- Deposits of up to 300 envelopes

ENHANCED SECURITY

Physical

- Security safes: CEN III or CEN III ExGas
- Variety of alarm options, e.g., DOCT
- Electronic or mechanical safe locks

Data

- Consumer awareness mirrors

Accessibility

- Compliant with regional height and reach requirements when mounted to the floor

Serviceability

- Rear load

Platform Software & Operating System

- ProBase/C
- Windows®

Application Software

- Vynamic® Software

INTERFACES

- Communication between DN Series® ATM and Night Drop Depository Sidecar

OPERATION

- 110 – 120 V; 220 – 240 V
- Frequency: 50/60 Hz

AMBIENT CONDITIONS

- Air temperature: -5° C to +40° C
- Humidity: 10% to 85%

SYSTEM AVAILABILITY

- DN Series® 200 and 250

DIMENSIONS

Measures (HxWxD) in millimeter

- Deposit sidecar:
1150 mm x 470 mm x 770 mm
- In trim (Deposit sidecar on floor):
1457 mm x 570 mm x 1120 mm

See installation manual for other configurations and installation parameters